



BUILDING DEPARTMENT
Waste Water
Division

Date Issued _____

Permit No. _____

Official Permit to Make Excavations in the Streets, Avenues and Alleys of the City of Creston, Iowa

Permission is hereby granted to _____
to make the necessary excavation for the purpose of connecting the property hereinafter described with the _____ system of said City, under the provisions of the Municipal Code of said City.

DESCRIPTION OF PROPERTY: (Residence, Store, Etc.) _____ at No. _____
_____ St. on Lot No. _____ Add.

Owner _____, Ph. _____

Main Sewer: Size _____, Grade _____, Direction _____, Location _____
_____, Depth _____ at date of construction _____ Record Page _____

CONNECTION PROVIDED FOR THIS PROPERTY WAS:

If this connection is to a sanitary sewer, you are to use 6" pipe in the public right of way and either 6" or 4" pipe in private property areas, using the following material; extra strength vitrified clay, cast iron or polyvinyl chloride (PVC), bedded with course sand or pea rock, conforming to ASTM 2665 schedule 40 or ASTM 1784 SDR 35 or less. Entire line shall be water tight.

Estimate of St. Dept. charges for damages caused: Refilling Excavation \$ _____

Replacing Paving \$ _____ Inspection Fees \$ _____ Total \$ _____

Applicant

Public Works Dept./Inspector

Inspection Record: By _____ Date _____

YOU ARE HEREBY ADVISED THAT you are to tell the Public Works Department of the exact time at which sewer lines are to be tapped and are not to disturb any sewer or accessory until the Public Works Department inspector, is personally on the ground to inspect the tap, and no portion of the sewer service shall be covered until the Public Works Department inspector has inspected the line.

From the point of connection with the main sewer to the building to be served, a raising grade of not less than 1% (1/8" per foot) must be maintained. If a "cut-in" connection to a sewer is permitted, top of first man hole down sewer from it must be uncovered at time of inspection.

If connection is to a sanitary sewer, no surface or subsurface drainage will be allowed.

YOU ARE FURTHER ADVISED that, from the time the excavation contemplated by this permit has been commenced until the work has been fully completed, you are to keep the obstruction safely barricaded and lighted for the protection of the public.

Owner should keep this permit with title papers and pass it with title, as information hereon may be great use to any one having future work to do on this connection.